



VFD004M11A



Model #:

Description								
(M Series) 1/2HP 0.373kW (CT 2.5A) / 3/4HP 0.559kW (VT 3A), 2.5/3A, 1 Ø 115VAC,0-400.00Hz (o/p), (V/Hz, SVC), IP20, Frame A2								
Manufacturer	Heavy Duty Output Rating		Light Duty Output Rating		-		Single Phase Duty Rating	
Delta Electronics	Input Amps Rating	9,0	Input Amps Rating	-	Input Amps Rating	-	1 Ø Input Amps Rating	9,0
	Rated HP	Rated Amps	HP	Rated Amps	HP	Rated Amps	HP	Amps
	0,5	2,5	0,5	2,5	-	-	0,5	3,0
	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps
Max. Capacity	0,5	3,0	0,5	3,0	-	-	0,5	3,0
Line Reactor	Heavy Duty		Light Duty		-		1 Ø Phase	
	Line	Load	Line	Load	Line	Load	Line	Load
Model	-	KDRMA22L1	-	KDRMA22L1	-	-	-	KDRMA22L1
HP Rating	-	0,50	-	0,50	-	-	-	0,50
Max Amps	-	5,0	-	5,0	-	-	-	5,0
Inductance uH	-	4200	-	4200	-	-	-	4200
Nema 1 Encl.Size	-	C1	-	C1	-	-	-	C1
Motor Models Compatible	Heavy Duty		Light Duty		-		1 Ø Phase	
	Model	HP	Model	HP	Model	HP	Model	HP
	MQR-124CW	0,5	-	-	-	-	MQR-344CW	0,75
	FLA	2,2	FLA	-	FLA	-	FLA	2,9
VFD Dimensions	Width (mm)	Width (in.)	Height (mm)	Height (in.)	Depth (mm)	Depth (in)	Wgt (Kg)	Wgt (lbs)
	100	3,937	151	5,94487	116,5	4,586605	1,5	3,48075
Input Voltage	Input Frequency	Input Phase	Enclosure		Control Method	V/Hz, Sensorless Vector		
100 ~ 120VAC (± 10%)	50/60Hz (±5%)	1	IP20					
Regulated Output Voltage	Efficiency	Motor Current Protection Range	Stall Prevention Level SHD / HD	Stall Prevention Level ND	Stall Prevention Level LD	Carrier Frequency	Accel / Decel Time	Default Rating
0.1 ~ 255Vac	≥97%	0.75 ~ 3 A	20 ~ 200%	-	-	1 ~ 15kHz	0.10 ~ 600.0 secs	Heavy Duty
Over Torque Level	DC Injection	Braking Chopper	Equivalent Braking Resistor Circuit	Minimum Braking Resistance Value	Starting Torque @			
30 ~ 200%	0 ~ 100.0 %	Builtin	80W 200Ω	80 Ω	V/Hz	SVC	VC+PG	
					10 ~ 200% @ 5Hz	10 ~ 200% @ 0.5Hz		
Analog Inputs			Analog Outputs			Keypad	Fault Record	Reel Time Stamp
AVI	ACI	AUI	AFM1	AFM2	DFM			
0 ~ 10vdc or 0/4 ~ 20ma	0 ~ 10vdc or 0/4 ~ 20ma	-	0 ~ 10vdc	-	-	Removable	3 last faults	No
Digital Inputs				Signal mode				
Dedicated	Safe Torque Off	Programmable	Control Voltage					
-	No	6	17vdc					
Digital Outputs				Built in Controllers				
DO1	DO2	DO3	DO4	Preset speeds	Process Control	PLC	PID	Position
1NO/NC Form C relay, ≤ 240VAC, ≤ 24vdc	Optocoupler NPN ≤ 48vdc	-	-	7	Yes	-	Yes	No
Communication				Built In Protocol 1	Built In Protocol 2	Built In Protocol 3		
Comm Port 1	Comm Port 2	Comm port 3	Comm port 4	Modbus ACSII	Modbus RTU	-		
RJ45 (RS-485)	-	-	-					
Options								
Option 1	VFD-PU06	Upload / Download Keypad, Compatible with all Delta Series except, V, VE,MS300, C2000, CP2000 series, RJ11 Comm port connectable						
Option 2	-							
Option 3	-							
Option 4	-							
Option 5	-							
Option 6	-							
Option 7	-							
Option 8	-							
Option 9	-							
Option 10	-							
Option 11	-							
Option 12	-							
Option 13	-							
Option 14	-							
Option 15	-							
Option 16	-							
Option 17	-							
Option 18	-							